

Wall-mount height-adjustable desk


Maintain >1" gap to adjacent furniture and fixed surfaces to eliminate any pinch points (*note: 1" pinch point on sides and 2" pinch points on back are designed in*)



Worksurface has a wood core with a high-pressure laminate or wood veneer surface and is 1.5" thick



Vertical swing doors are equally sized and provide easy access for installation, cables, etc.



Lifting Column is controlled by a central control box for synchronization


Columns are precision balanced to minimize surface vibration

3 Preset Programmable Controller is standard and mounted under the desk

Active or Simple Touch Controller may be requested via Specials


Foundation case is 10" deep and conceals the lifting columns

CPU or other equipment may be stored within



corner desk

Details




3 mm edge profile

Laminate worksurface with plastic edge:

- square edge profile
- 3 mm plastic edge on user and visitor sides
- 1 mm plastic edge on other sides

Wood worksurface with wood edge:


- square edge profile
- 3 mm veneer edge on user and visitor sides
- .5 mm veneer edge on other sides



GRAIN DIRECTION

Foundation - Vertical grain direction is the default on the foundation case, but horizontal grain may be selected for both veneer and laminate.

Grain direction for FOUNDATION CASE TOP defaults to match the grain direction of the worksurface. If another solution is needed, please contact Specials.



Straight Desk:

Top (Laminate)

Long grain direction is the default on worksurfaces, but short grain may be selected for worksurfaces 60"W and smaller.

Top (Veneer)


Long grain direction is the default on worksurfaces, but short grain may be selected.

Corner Desk:

All notes from Straight Desk apply in addition to the following:

Top (Laminate + Veneer)

Short grain direction is the default on return worksurfaces, but long grain may be selected.



Cable Management:

- 1 The molded felt cover helps manage wires underneath the worksurface (e.g. base controller wires). (Two molded felt covers provided with corner desk.)
- 2 The cable riser (vertebrate) helps manage wires that go into the foundation (e.g. user power, etc).



Wall Requirements:

See the Wall-mount HAD assembly instructions for minimum recommendations. However, mounting hardware is to be specified/verified by the Engineer of Record or approved by approver having jurisdiction.

Surface Materials

All available Elective Elements laminates and veneers are available on desk itself. Refer to the Elective Elements specification guide for more details. COLs are also allowed. The lifting column is available only in 4799 Platinum and 0835 Black.

Pricing

	Style Number	Size	Door Size	List Price* Laminate (PL 202)	List Price* Veneer (PL 202)
Wall-mount HAD straight 	STUWDKWAL3042	30"D x 42"W	14"W	\$5,319	\$6,221
	STUWDKWAL3048	30"D x 48"W	16"W	\$5,403	\$6,335
	STUWDKWAL3054	30"D x 54"W	18"W	\$5,487	\$6,445
	STUWDKWAL3060	30"D x 60"W	20"W	\$5,571	\$6,561
	STUWDKWAL3066	30"D x 66"W	22"W	\$5,654	\$6,674
	STUWDKWAL3072	30"D x 72"W	24"W	\$5,739	\$6,785
	STUWDKWAL3078	30"D x 78"W	19.5"W	\$6,012	\$7,090
	STUWDKWAL3084	30"D x 84"W	21"W	\$6,110	\$7,214
Wall-mount HAD corner 	STUWDKWALCRNR	30"DL x 54"WL x 30"DR x 84"WR	24"W	\$7,846	\$9,281

* Price may change based on options selected.

FAQs

What is the pinch point guideline for the Wall-mount HAD? 1" application rules apply similar to other HADs.

Is there an obstruction sensor?

No, however the lifting column will slow down during the last ~4.5" of travel.

Can Active Touch be offered as a special?

Yes, both Active Touch and Simple Touch may be specified via Specials.

Does Wall-mount HAD hit BIFMA range?

No, however, if you add a keyboard, this may meet the BIFMA range.

What is the height range for Wall-mount HAD?

Height range of single stage is 27.7" - 47.4".

What is the maximum height for storage?

Wall-mount HAD will accommodate a 1.5 high storage (sold separately). The height range to the TOP of the worksurface is 27.7" and worksurfaces are 1.5" thick. Be sure to factor in cable trough and a 1" pinch point.

What is the maximum weight capacity?

Dependent on which size. For the largest model, net of the worksurface, 185 lbs.

What is the depth and height of the foundation case?

About 10" x 23" nominal. This makes installation simple and also allows for a CPU, wires, etc.

Can I use the foundation case for storage?

No, we recommend this be left empty for IT access, but a CPU and other IT could be stored there. It is not practical for items such as books.

Can I get a thicker top on the foundation case to match the worksurface?

Yes, please submit a request via Specials.

What color does the lifting column come in?

0835 Black and 4799 Platinum.

Can monitor arms be used?

Yes, any Steelcase monitor arms can be used (both clamp-mounted and through-mounted). Be mindful of the 1" pinch point requirement.

Can I add a pencil lip?

Generally, yes, but this request would be processed via Specials RFQ.

Can I clamp on a power unit?

Yes. Be mindful of the 1" pinch point requirement.

How do I route cords beneath the surface?

Cords can be routed inside the molded felt cable trough.

Can I get the desks with grommets factory installed?

Yes, you can order these through Specials. Simply refer to the appropriate style number when you put your request in.

What height do the outlets need to be to fit within the foundation and not interfere with the wall attachment? There is a continuous open space across the back of the foundation from 10.25" to 19" above finish floor for data and power port access (measured with glides fully recessed).

What are the wall requirements for mounting? Backing?

See the Wall-mount HAD assembly instructions for minimum recommendations. However, mounting hardware is to be specified/verified by the Engineer of Record or approved by approver having jurisdiction.

Can the Wall-mount HAD be attached to VIA or Privacy wall? This is yet to be determined. If you have a specific case, contact Steelcase Studio and we can get you an answer.

Is plywood edgeband available?

Yes.

Can you specify a blade edge surface through Specials?

Yes.

Can you specify a Universal thickness surface through Specials?

Yes.

Is laminate offered in short grain on the worksurface?

Worksurfaces under 60" can be ordered in short grain.

Can you mix materials - for example a wood foundation and a laminate top?

Yes, the worksurface and foundation case are both specifiable.

Can you mix two different laminates or two different veneers for the top and foundation case?

Yes, the worksurface and foundation case are both specifiable.



For more information visit steelcase.com or email us at studiob@steelcase.com.